



THE
HOTEL COLLECTION



by

 **GERARD**[®]
ROOFING SYSTEMS

ADDING VALUE TO YOUR HOTEL

ASTHETICS



The consistent vibrant colour of a Gerard® Roof combined with natural stone coating gives your guests the impression of a well managed luxury hotel where guest comfort and the environment enjoy equal priority

MAINTENANCE FREE



Gerard® tiles require little to no maintenance, and are designed to withstand weather extremes. A Gerard® roof will continue to communicate your brand values for generations to come without any major refurbishment work

FIRE RESISTANT



Gerard® Roofing Systems are chosen by hotels throughout the world for their fire resistant properties. Tested to international standards and certified by ASTM & UL



The Hotel Collection by Gerard®

GERARD® ROOFING SYSTEMS HAS A LONG HISTORY OF WORKING CLOSELY WITH HOTELS THROUGHOUT AFRICA TO ACHIEVE ROOFING SOLUTIONS THAT NOT ONLY LOOK GOOD BUT PERFORM TO THE HIGHEST OF STANDARDS, KEEPING BOTH HOTEL AND **GUESTS SAFE AND SECURE.**

OUR **NATURAL VOLCANIC STONE COATING** RETAINS ITS VIBRANT COLOUR DESPITE HARSH UV EXPOSURE AND OUR **ALU-ZINC STEEL** THRIVES IN COASTAL ENVIRONMENTS WITHOUT THE RISK OF RUST OR CORROSION.

WITH A CHOICE OF SIX DIFFERENT PROFILES, EACH WITH THEIR OWN PERSONALITY, AND OVER 30 COLOURS, IT'S EASY TO FIND A GERARD® ROOF TO COMPLIMENT THE LOOK AND FEEL OF YOUR ESTABLISHMENT AND **REFLECT THE PRESTIGE OF YOUR BRAND.**

WORKING WITH GERARD® COULDN'T BE EASIER; WITH EXCLUSIVE DISTRIBUTORS THROUGHOUT SUB-SAHARAN AFRICA WE HAVE THE EXPERIENCE AND EXPERTISE WHEREVER YOU ARE. TO DISCOVER MORE ABOUT GERARD®, OR FIND YOUR LOCAL OFFICE PLEASE VISIT US AT WWW.GERARDAFRICA.COM

MAKE SHARE IT'S
#GenuineGerard



HERITAGE
GREENSTONE



HERITAGE
SAPPHIRE



SHINGLE
SUNSET



SHAKE
PEPPER

PERFORMANCE



FIRE

- Class a and b under UL 790 (ASTM E-108) when applied in accordance with instructions
- Tested up to 760oc.



HURRICANE

- Hurricane Test by Construction Research Laboratory Inc, Miami, Florida, USA.
- Tested against 200kph winds.



FAST INSTALLATION

Quick installation times can lead to further cost savings in the construction of your hotel.



LIGHTWEIGHT

- 7.0 KG/M²
- One ton of Gerard® tiles is equivalent to 7 tons of clay or concrete tiles!



STRONG

Concentrated Force on Roofing Tiles to Australian Standard 1582, Rule 5.2 by Cyclone Testing Station, Australia.



CORROSION

- Salt/fog Test to ASTM B117.
- 100% Relative Humidity Test to ASTM D2247



HAIL

Hailstone Test by Commonwealth Scientific and industrial Research Organization, Division of building, Construction and Engineering, Australia.



SECURITY

An overlapping Gerard® roof tile is secured to the two tiles on either side, the above tile, the below tile and the rafter - making a Gerard® roof tile incredibly secure.



RAIN (MONSOON)

Cyclone Loading Test to wind loading code, Australian Standards 1170, Part 1 1975 by Cyclone Loading Station, Australia.



 **GERARD**[®]
ROOFING SYSTEMS